



A1104T

IP VIDEO INDOOR STATION

Premium door communication for luxury homes and residential, commercial and public properties.
With built-in hearing loop, for hearing impaired people.

The A1104T IP Video Indoor Station blends luxury with cutting-edge technology. Crafted from premium materials with a sleek, modern design, it offers HD video and audio calls, seamless door and gate control, and advanced features including smart home integration.

The DoorBird Indoor Station features a scratch-resistant tempered glass touch display and an intuitive, user-friendly interface, ensuring effortless operation with elegance and style.

The hearing loop of the A1104T sends the audio signal from the indoor station directly to residents' hearing aids, ensuring clear communication for all users.





Configurable tile view

TECHNICAL INNOVATION

7" True IPS Touch Display with HD video and two-way audio ensure crystal-clear communication. Network connectivity via LAN (PoE) and WiFi offers flexible installation. Integrated relays and digital inputs enable smart home integration.

CONFIGURABLE LED STATUS BAR AND STAINLESS STEEL PANEL

The configurable RGB LED status bar signals visitors and missed calls. Multiple mounting options ensure adaptability to various interiors. The stainless steel accent at the bottom front brings a premium feel that complements any stylish space.



Configurable LED status bar



SMART FEATURES

- Door opener and elevator control
- Visitor history (free Cloud Recording)
- Room to room communication, when using several Indoor Stations
- SIP support, e.g. for concierge or facility manager calls
- Weather forecast display
- Home and building automation control (IP, TCP, HTTPS, relays etc.)
- Configurable via the DoorBird App and web-based dashboard, worldwide
- Compatible with smart locks and the DoorBird IP Video Mini Dome Camera
- Built-in hearing loop

TECHNICAL SPECIFICATIONS

GENERAL

Material	Polycarbonate, glass, stainless steel Stainless steel cover available in various colors and finishes
Mounting type	Surface-mounted, table stand sold separately
Power supply	15 - 48 V DC (min. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)
Weight	580 g
Connectors	<ul style="list-style-type: none"> • RJ45, for LAN/PoE • Digital input (0 V, 0 A (NO)) #1, e.g. for storey-call button • Digital input (0 V, 0 A (NO)) #2, e.g. for second storey-call button • Bistable latching relay #1, max. 24 V DC/AC, 1 A, e.g. for electric door opener or elevator • Bistable latching relay # 2, max. 24 V DC/AC, 1 A, e.g. for electric door opener or elevator • 15 - 48 V DC input (+, -), max. 15 W
Power consumptions	max. 10 W
Approvals	CE RED (EMC,RF,Health, Safety), IEC/EN 62368, FCC, IC, Reach 250, RoHs 2.0, California 65, WEEE
Dimensions	146 x 185 x 26,04 mm (H x W x D) 5.75 x 7.28 x 0.72 in (H x W x D)
Operating conditions	0 to +55°C / 32 to 131°F Humidity 0 % to 85 % (non condensing)
Scope of delivery	<ul style="list-style-type: none"> 1x IP Video Indoor Station 1x Mounting bracket 1x Power supply unit (mains adaptor) with up to four country-specific adaptors (100 - 240 V AC to 15 V DC) 1x Quickstart guide with Digital Passport 1x Installation manual 1x Small parts
EAN	4251489614073
Warranty	see www.doorbird.com/warranty

CURRENT SYSTEM REQUIREMENTS

System requirements	<p>Mobile device: Newest iOS on iPhone/iPad, newest Android on Smartphone/Tablet</p> <p>Internet: High-Speed Landline Broadband Internet connection, DSL, cable or fiber optic, no socks or proxy server</p> <p>Network: Ethernet Network, with DHCP</p>
Supported door stations	Any DoorBird IP Video Door Station

DISPLAY

Dimensions	7" True Color LCD
Touch	Yes, capacitive
Resolution	1024 x 600 px
IPS	Yes

AUDIO

Audio components	Speaker and microphone, echo and noise cancellation (AEC, ANR)
Audio streaming	Two-way
Induction loop	Yes

NETWORK

Ethernet	PoE IEEE 802.3at, 10/100 Base-T
WiFi	802.11 b/g/n 2.4 GHz

INTEGRATED WIRELESS MODULES

WiFi	802.11 b/g/n 2.4 GHz
Induction loop	For hearing aids

OPTIONAL ACCESSORIES

Sold separately	see www.doorbird.com/buy
-----------------	--

QUICK AND EASY INSTALLATION ON:



