

# HELULIGHT® CLASSIC-RGB 1120

Art. Nr. 11024048

ID 1-000000-06984

EAN Nr. 4260654163438



## Normen / Norms

DIN EN 60598-1 :2021/A11:2022

DIN EN 60529 :1991/A2:2013/AC:2019-02

DIN EN 55015:2019+A11:2020

DIN EN IEC 63000:2018

DIN EN 61547:2009

DIN EN 62471:2009



## Elektrische Rahmenbedingungen / Electrical characteristic


Netzanschluss / Main Supply	24 VDC
Leistung / Power (R G B)	8,4W   3,6W   9,6W
Dimmbar / Dimmable	PWM
Anschluss / Connection Type	M8, 4-Pol, A-Cod.
Durchschleifbar / Loopthrough	Nein / No
Pinbelegung / Pin assignment	

## Licht / Light

Bestückt / Fitted With	LED
Lichtfarbe / Light Colour	-
Lichstrom(Brutto) / Lum. Flux(Gross)(R G B)	236lm   404lm   168lm
Lichstrom(Netto) / Lum. Flux(Net)(R G B)	177lm   286lm   115lm
Effizienz(Brutto) / Efficiency(Gross)(W)	-
Effizienz(Netto) / Efficiency(Net)(W)	-
Abstrahlwinkel / Beam Angle	120°
Farbtreue / Colour Rendering	-
Photobiological Safety	RG-1

## Mechanik / Mechanics

Gehäuse / Housing	Aluminium
Abdeckung / Cover	PMMA, Diff.
Drehbar / Rotatable	Ja / Yes
Gewicht(Netto) / Weight(Net)	0,59 kg
Betriebstemperatur / Operating Temp.	-20°C / +50°C
Lebensdauer / Lifetime	min. 60000 h
Befestigung / Fastening	2x Endhalter / 2x Brackets



a = 1130mm b = 1146,5mm

\*Technische Änderungen vorbehalten | technical modifications reserved