

KNX-RF COMPATIBLE PRODUCTS

Switching actuator 1-channel paladin 672 730 rf



Overview

- Switching actuator 1-channel
- Functions: Switching (on/off), Timer (3sec. - 10min.)
- Breaking capacity: 250V / 16A
- Adjustable Timer from 3 seconds to 10 minutes
- Additional input for wired push button
- RF-repeater function included
- DIN-rail mounting
- Protection class IP20
- KNX-RF compatible

Order numbers

■ paladin

672 730 rf Switching actuator
1-channel

Technische Änderungen vorbehalten.

KNX-RF COMPATIBLE PRODUCTS

Switching actuator 1-channel paladin 672 730 rf

Technical data

Supply voltage	230V~ 50Hz
Power consumption	35 mA
Breaking capacity	16A 250V (cos $\varphi=1$)
Transmission type	Codified transmission in 868,4MHz with ERP>8mW and a coverage of 100m (in the free field)
Operating modes	Switching (ON/OFF) Timer
Timer delay	00:03 to 10:00 mm:ss
KNX-RF compatible commands	CH_Light_Actuator_Scene (0103h)
Permitted ambient temperature	-10°...+45°C
Dimensions	1 module wide (17,5mm)
Mounting	35 mm DIN-rail
Connection type	Screw-type terminal
Protection degree	IP20

Technische Änderungen vorbehalten.

